



US005974349A

**United States Patent [19]**

Levine

**Patent Number: 5,974,349****Date of Patent: \*Oct. 26, 1999****[54] REMOTE, AIRCRAFT, GLOBAL, PAPERLESS MAINTENANCE SYSTEM****[76] Inventor:** Seymour Levine, 21645 Saddle Peak Rd., Topanga, Calif. 90290**[\*] Notice:** This patent is subject to a terminal disclaimer.**[21] Appl. No.:** 09/205,331**[22] Filed:** Dec. 4, 1998**Related U.S. Application Data****[63]** Continuation of application No. 08/768,313, Dec. 17, 1996, Pat. No. 5,890,079.**[51] Int. Cl. 4** G06F 19/00**[52] U.S. Cl.** 701/29; 701/14; 701/35;

340/945

**[58] Field of Search** 701/14, 29, 35, 701/120, 301; 340/945, 961, 963, 971;

342/29, 36, 37, 38, 454, 455, 456

**[56] References Cited****U.S. PATENT DOCUMENTS**

4,729,102	3/1988	Miller, Jr. et al.	701/14
5,153,836	10/1992	Fraughton et al.	701/301
5,325,302	6/1994	Izidon et al.	701/301
5,383,133	1/1995	Staple	340/963
5,463,656	10/1995	Polvka et al.	375/200
5,467,274	11/1995	Vax	701/14
5,493,309	2/1996	Bjornolt	701/301

**Primary Examiner—Gary Chin  
Attorney, Agent, or Firm—Norton R. Townsley****[57] ABSTRACT**

This invention is a system that monitors many performance parameters and many aircraft operational parameters, and broadcasts this information along with aircraft identification, audio, video, global positioning and altitude data, to a world wide two-way network. This information is monitored and recorded at a remote, centralized location. At this location, this information is combined with archived data, ATC data, weather data, topographic data, map data, and manufacturers' data. Analysis of this combined data allows identification of problems and generation of advisories. Six types of advisories are generated: maintenance, safety of flight, flight efficiency, flight separation, safe to fly and safe to take off. In the event of a crash the remotely recorded data provides an instant indication of the cause of the crash as well as where the crashed plane can be found. Use of this invention allows replacement of the current, on-board flight data recorders thus saving costs and weight. Having the recorded data at a remote site eliminates the need to search for flight data recorders. Other advantages are back-up for ATC radar position data, better control of aircraft separation, improved flight efficiency, and allowing use of simpler and lower power radar.

**3 Claims, 4 Drawing Sheets**